# **Appendix E.** Calibration Certificates



### Sun Creation Engineering Limited

Calibration and Testing Laboratory

# Certificate of Calibration 校正證書

Certificate No.: C173907

Date of Receipt / 收件日期: 11 July 2017

證書編號

ITEM TESTED / 送檢項目 (Job No. / 序引編號: IC17-1606)

Description / 儀器名稱

Integrating Sound Level Meter

Manufacturer / 製造商

Brüel & Kjær

Model No. / 型號

2238

Serial No. / 編號

2800932

Supplied By / 委託者

Atkins China Limited

13/F., Wharf T&T Centre, Harbour City, Tsim Sha Tsui, Kowloon, Hong Kong

TEST CONDITIONS / 測試條件

Temperature / 温度 :

 $(23 \pm 2)^{\circ}$ C

Relative Humidity / 相對濕度 :

 $(55 \pm 20)\%$ 

Line Voltage / 電壓

TEST SPECIFICATIONS / 測試規節

Calibration check

DATE OF TEST / 測試日期

17 July 2017

TEST RESULTS / 測試結果

The results apply to the particular unit-under-test only.

The results do not exceed manufacturer's specification.

The results are detailed in the subsequent page(s).

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory
- Agilent Technologies / Keysight Technologies
- Rohde & Schwarz Laboratory, Germany
- Fluke Everett Service Center, USA

Tested By

測試

K C Lee Engineer

Certified By

核證

H C Chan

Date of Issue 簽發日期

17 July 2017

Engineer

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書而批准。



### Sun Creation Engineering Limited

Calibration and Testing Laboratory

# Certificate of Calibration 校正證書

Certificate No.:

C173907

證書編號

1. The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 12 hours, and switched on to warm up for over 10 minutes before the commencement of the test.

2. Self-calibration using the B & K Acoustic Calibrator 4231, S/N: 3004068 was performed before the test.

3. The results presented are the mean of 3 measurements at each calibration point.

4. Test equipment:

Equipment ID

CL280 CL281 Description

40 MHz Arbitrary Waveform Generator Multifunction Acoustic Calibrator

Certificate No. C170048 PA160023

5. Test procedure: MA101N.

6. Results:

6.1 Sound Pressure Level:

6.1.1 Reference Sound Pressure Level

|            | UUT              | Setting                |                   | Applied Value |                | UUT          | IEC 61672 Class 1 |
|------------|------------------|------------------------|-------------------|---------------|----------------|--------------|-------------------|
| Range (dB) | Parameter        | Frequency<br>Weighting | Time<br>Weighting | Level (dB)    | Freq.<br>(kHz) | Reading (dB) | Spec.             |
| 50 - 130   | L <sub>AFP</sub> | A                      | F                 | 94.00         | 1              | 94.1         | ± 1.1             |

6.1.2 Linearity

| UUT Setting |                  |                        |                   | Applied    | Value          | UUT          |  |
|-------------|------------------|------------------------|-------------------|------------|----------------|--------------|--|
| Range (dB)  | Parameter        | Frequency<br>Weighting | Time<br>Weighting | Level (dB) | Freq.<br>(kHz) | Reading (dB) |  |
| 50 - 130    | L <sub>AFP</sub> | A                      | F                 | 94.00      | 1              | 94.1 (Ref.)  |  |
|             |                  |                        |                   | 104.00     |                | 104.1        |  |
|             |                  |                        |                   | 114.00     |                | 114.1        |  |

IEC 61672 Class 1 Spec. :  $\pm$  0.6 dB per 10 dB step and  $\pm$  1.1 dB for overall different.

6.2 Time Weighting

| UUT Setting |                  |                        |                   | Applied Value          |   | UUT          | IEC 61672 Class 1 |
|-------------|------------------|------------------------|-------------------|------------------------|---|--------------|-------------------|
| Range (dB)  | Parameter        | Frequency<br>Weighting | Time<br>Weighting | Level Freq. (dB) (kHz) |   | Reading (dB) | Spec. (dB)        |
| 50 - 130    | L <sub>AFP</sub> | A                      | F                 | 94.00                  | 1 | 94.1         | Ref.              |
|             | L <sub>ASP</sub> |                        | S                 |                        |   | 94.1         | ± 0.3             |

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory.

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書面批准。



### Sun Creation Engineering Limited

Calibration and Testing Laboratory

# Certificate of Calibration 校正證書

Certificate No.: C173907

證書編號

6.3 Frequency Weighting

6.3.1 A-Weighting

|            | UUT Setting |                        |                   |            | Applied Value |              | IEC 61672 Class 1 |
|------------|-------------|------------------------|-------------------|------------|---------------|--------------|-------------------|
| Range (dB) | Parameter   | Frequency<br>Weighting | Time<br>Weighting | Level (dB) | Freq.         | Reading (dB) | Spec.             |
| 50 - 130   | $L_{AFP}$   | A                      | F                 | 94.00      | 63 Hz         | 67.9         | $-26.2 \pm 1.5$   |
|            |             |                        |                   |            | 125 Hz        | 77.9         | $-16.1 \pm 1.5$   |
|            |             |                        |                   |            | 250 Hz        | 85.4         | $-8.6 \pm 1.4$    |
|            |             |                        |                   |            | 500 Hz        | 90.8         | $-3.2 \pm 1.4$    |
|            |             |                        |                   |            | 1 kHz         | 94.1         | Ref.              |
|            |             |                        |                   |            | 2 kHz         | 95.3         | $+1.2 \pm 1.6$    |
|            |             |                        |                   |            | 4 kHz         | 95.1         | $+1.0 \pm 1.6$    |
|            |             |                        |                   |            | 8 kHz         | 92.9         | -1.1 (+2.1; -3.1) |
|            |             |                        |                   |            | 12.5 kHz      | 89.8         | -4.3 (+3.0; -6.0) |

6.3.2 C-Weighting

|               | UUT Setting |                        |                   |            | Applied Value |              | IEC 61672 Class 1  |
|---------------|-------------|------------------------|-------------------|------------|---------------|--------------|--------------------|
| Range<br>(dB) | Parameter   | Frequency<br>Weighting | Time<br>Weighting | Level (dB) | Freq.         | Reading (Db) | Spec. (dB)         |
| 50 - 130      | $L_{CFP}$   | С                      | F                 | 94.00      | 63 Hz         | 93.3         | $-0.8 \pm 1.5$     |
|               |             |                        |                   |            | 125 Hz        | 93.9         | $-0.2 \pm 1.5$     |
|               |             |                        |                   |            | 250 Hz        | 94.0         | $0.0 \pm 1.4$      |
|               |             |                        |                   |            | 500 Hz        | 94.0         | $0.0 \pm 1.4$      |
|               |             |                        |                   |            | 1 kHz         | 94.0         | Ref.               |
|               |             |                        |                   |            | 2 kHz         | 93.9         | -0.2 ± 1.6         |
|               |             |                        |                   |            | 4 kHz         | 93.2         | $-0.8 \pm 1.6$     |
|               |             |                        |                   |            | 8 kHz         | 90.9         | -3.0 (+2.1; -3.1)  |
|               |             |                        |                   |            | 12.5 kHz      | 87.8         | -6.2 (+3.0 ; -6.0) |

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可溯源至國際標準,局部複印本證書需先獲本實驗所書而批准。



#### Sun Creation Engineering Limited

Calibration and Testing Laboratory

# Certificate of Calibration 校正證書

Certificate No.: C173907

證書編號

Remarks: - UUT Microphone Model No.: 4188 & S/N: 2793199

- Mfr's Spec. : IEC 61672 Class 1

- Uncertainties of Applied Value : 94 dB : 63 Hz - 125 Hz :  $\pm$  0.35 dB

104 dB : 1 kHz :  $\pm$  0.10 dB (Ref. 94 dB) 114 dB : 1 kHz :  $\pm$  0.10 dB (Ref. 94 dB)

- The uncertainties are for a confidence probability of not less than 95 %.

#### Note:

Only the original copy or the laboratory's certified true copy is valid.

The values given in this Certificate only relate to the values measured at the time of the test and any uncertainties quoted will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the measurement. Sun Creation Engineering Limited shall not be liable for any loss or damage resulting from the use of the equipment.

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory.

本證書所載校正用之測試器材均可溯源至國際標準。局部複印本證書需先獲本實驗所書而批准。



#### Sun Creation Engineering Limited

Calibration and Testing Laboratory

# Certificate of Calibration 校正證書

Certificate No.:

C173906

證書編號

ITEM TESTED / 送檢項目 (Job No. / 序引編號: IC17-1606)

Date of Receipt / 收件日期: 11 July 2017

Description / 儀器名稱

Acoustical Calibrator

Manufacturer / 製造商

Brüel & Kjær

Model No. / 型號 Serial No./編號

4231 3004068

Supplied By / 委託者

Atkins China Limited

13/F., Wharf T&T Centre, Harbour City, Tsim Sha Tsui, Kowloon, Hong Kong

TEST CONDITIONS / 測試條件

Temperature / 溫度

 $(23 \pm 2)^{\circ}$ C

Relative Humidity / 相對濕度 :

 $(55 \pm 20)\%$ 

Line Voltage / 電壓 :

TEST SPECIFICATIONS / 測試規範

Calibration check

DATE OF TEST / 測試日期

17 July 2017

TEST RESULTS / 測試結果

The results apply to the particular unit-under-test only.

The results do not exceed manufacturer's specification.

The results are detailed in the subsequent page(s).

The test equipment used for calibration are traceable to National Standards via:

- The Government of The Hong Kong Special Administrative Region Standard & Calibration Laboratory
- Agilent Technologies / Keysight Technologies
- Rohde & Schwarz Laboratory, Germany
- Fluke Everett Service Center, USA

Tested By

測試

K C/Lee

Certified By

核證

Engineer

H C Chan

Engineer

Date of Issue

17 July 2017

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory

本證書所載校正用之測試器材均可測源至國際標準。局部複印本證書需先獲本實驗所書面批准。



#### Sun Creation Engineering Limited

Calibration and Testing Laboratory

# Certificate of Calibration 松工惑事

Certificate No.:

C173906

證書編號

校正證書

1. The unit-under-test (UUT) was allowed to stabilize in the laboratory for over 12 hours before the commencement of the test.

2. The results presented are the mean of 3 measurements at each calibration point.

3. Test equipment:

Equipment ID CL130 CL281 TST150A Description

Universal Counter

Multifunction Acoustic Calibrator Measuring Amplifier Certificate No.

C173864 PA160023 C161175

4. Test procedure: MA100N.

5. Results:

5.1 Sound Level Accuracy

| Journa Dever Meeting |                |             |                               |
|----------------------|----------------|-------------|-------------------------------|
| UUT                  | Measured Value | Mfr's Spec. | Uncertainty of Measured Value |
| Nominal Value        | (dB)           | (dB)        | (dB)                          |
| 94 dB, 1 kHz         | 94.0           | ± 0.2       | ± 0.2                         |
| 114 dB, 1 kHz        | 114.0          | N           |                               |

5.2 Frequency Accuracy

| Frequency Accuracy |                |                            |                               |
|--------------------|----------------|----------------------------|-------------------------------|
| UUT Nominal Value  | Measured Value | Mfr's                      | Uncertainty of Measured Value |
| (kHz)              | (kHz)          | Spec.                      | (Hz)                          |
| 1                  | 1,000,0        | $1 \text{ kHz} \pm 0.1 \%$ | ± 0.1                         |

Remark: The uncertainties are for a confidence probability of not less than 95 %.

Note:

Only the original copy or the laboratory's certified true copy is valid.

The values given in this Certificate only relate to the values measured at the time of the test and any uncertainties quoted will not include allowance for the equipment long term drift, variations with environment changes, vibration and shock during transportation, overloading, mis-handling, or the capability of any other laboratory to repeat the measurement. Sun Creation Engineering Limited shall not be liable for any loss or damage resulting from the use of the equipment.

The test equipment used for calibration are traceable to the Nation Standards as specified in this certificate. This certificate shall not be reproduced except in full, without the prior written approval of this laboratory.

本證書所載校正用之測試器材均可測源至國際標準。局部複印本證書需先獲本實驗所書而批准。